

# Turbo Barb Fittings

## Features & Benefits



**Special Connector for 20 mm**

Special one piece connector designed for 20 mm tube



**Three Barb Connector**

Equipped with Three barbs to prevent snap out from tube

## Additional Features

- Manufactured from tough engineering plastic
- Non corrosive & resistant to chemicals
- UV resistant fittings

## Applications

Feasible for thick wall thickness Polytubes (plain Lateral / Jain Tough Hose) as well as Dripline tubes for following specifications

Nominal Diameter (mm)	Inner Diameter (mm)	Wall thickness (mm)
20	18	0.7 - 1.7
20	18.2	0.9 - 1.7

## Turbo Barb Joiner



Tube Size (mm)	Code	Bag	Box		
		Qty. (nos.)	Qty. (nos.)	Wt. (kg)	Code
20 mm	JOTB20	100	2000	14.3	B

## Turbo Barb Take off



Tube Size (mm x mm)	Code	Bag	Box		
		Qty. (nos.)	Qty. (nos.)	Wt. (kg)	Code
20 OD x 13	TOTB2013	100	2000	11.9	B

## Turbo Barb Tee



Tube Size (mm)	Code	Bag	Box		
		Qty. (nos.)	Qty. (nos.)	Wt. (kg)	Code
20 OD	TBTO20	50	800	9.0	B

## Turbo Barb Elbow



Tube Size (mm)	Code	Bag	Box		
		Qty. (nos.)	Qty. (nos.)	Wt. (kg)	Code
20 OD	TBELO20	50	1500	12.0	B

## Turbo Barb Threaded Tee



Tube Size (mm x inch x mm)	Code	Bag	Box		
		Qty. (nos.)	Qty. (nos.)	Wt. (kg)	Code
20OD x 1/2" x 20OD	TBT02012	50	800	7.0	B
20OD x 3/4" x 20OD	TBT02034	50	700	10.0	B
20 OD x 1" x 20 OD	TBT20100	50	500	9.0	B

## Turbo Barb Adaptor



Size (inch x mm)	Code	Bag	Box		
		Qty. (nos.)	Qty. (nos.)	Wt. (kg)	Code
1/2" x 20 OD	TBAO2012	50	1200	11.3	B
3/4" x 20 OD	TBAO2034	50	1200	11.0	B
1" x 20 OD	TBAO2001	50	800	12.0	B