







Innovative Sprinkler Design Compact, sturdy, closed and full- or part-circle geardriven sprinkler



Special filter on Sprinkler Removable filter screen eliminates nozzle clogging.



Gear-driven mechanism Gear-driven mechanism provides quiet operation, ideal for early morning or late night irrigation



Easy fingertip adjustment User-friendly, fingertip adjustment to full- or part-circle



Innovative Baffle deflector Innovative Baffle deflector allows radius adjustment: 5.0 to 11.5m



Bayonet nozzles Bayonet nozzles with integrated stream straightening vanes in nozzles for maximum throw

Acurain 525

Additional Features

- Excellent Precipitation: Gentle precipitation, no damage to flowers / plants
- Quality Comes First: Each batch is tested for stringent quality parameters
- Water lubrication provides reliable, long-lasting operation.

Applications

For residential and small public areas, also as hose-end on spike or sled bases

Specifications

- Discharges : 510 to 1180 lph
- Diameter : 20m to 23m
- \bullet Recommended Pressure : 2.0 kg/cm² to 4.0 kg/cm²
- Inlet Connection : 1/2" BSP male threaded

Technical Specification

Nozzle Color	P (kg/cm²)	Q (lph)	D
			(m)
3.0* Orange	2.0	510	20.0
	3.0	630	21.0
	4.0	720	22.0
3.2* Green	2.0	570	20.0
	3.0	700	21.5
	4.0	810	22.0
4.0* Red	2.0	850	21.0
	3.0	1030	22.0
	4.0	1180	23.0

Acurain 525 Assembly





